

MAC PERMAHOT LASER

ELECTRICALLY HEATED PRESSURE WASHER

UNIQUE TO THE INDUSTRY

- Electrically Heated
- Permanent Hot Water
- 90°C Constant Temperature
- Low Water Consumption



KEY SPECIFICATION

Hot Water

6ltr/min Water Flow

150bar Pressure

90°C Constant Temperature

415v, 32amp Power Supply

PERMAHOT

MAC PERMAHOT LASER

ELECTRICALLY HEATED PRESSURE WASHER

PERMAHOT



STANDARD FEATURES

- 90°C Constant Temperature
- Patented 3 x 4kw Hollow Element system
- Full stainless steel chassis and cover
- Front and rear chassis protection bars
- 4 large robust wheels for tough terrain
- Professional Interpump with ceramic pistons
- Industrial 1450rpm low rewing electric motor
- Instant stop system
- Stainless steel water tank with low water cut off switch
- Water softener system
- Bypass valve
- Pressure gauge
- Heater on/off switch
- Mains on lamp & heating element lamp
- Heater controlled by thermostat
- 24v low tension safety controls
- Current thermal overload protection
- Stainless steel manual hose reel & stainless steel basket for accessories
- Plastic lance holders
- Including 15mt hose, 900mm quick release lance and heavy duty trigger

		MAC64
TECHNICAL INFORMATION	Water Flow	6lt per minute
	Pressure	150bar, 2200psi
	Motor Specification	5.5hp, 1450rpm
	Shutdown System	Instant Stop
	Temperature	0-90°C Constant
	Power	415v, 32amps
	Weight	100kg
	Dimensions (h x w x d)	97 x 60 x 106cm

The Permahot Laser utilises our patented 3 x 4kw hollow element heating system.

It is now possible to produce 90°C constant heat, indefinitely, on a standard 415v, 32amp power supply.

Perfect for food environments and all conditions where diesel, fumes and large water consumption are major problems.

WASHMASTER RANGE ELECTRICALLY HEATED PRESSURE WASHERS



MAC PERMAHOT LASER



MAC PERMAHOT STATIC



MAC ELEKTRA